

*Indian Standard*

**CONCRETE POLES FOR OVERHEAD POWER  
AND TELECOMMUNICATION LINES —  
METHODS OF TEST**

*( First Revision )*

भारतीय मानक

शिरोपी पावर तथा दूरसंचार लाइनों के लिए कंकरीट के खम्भे — परीक्षण पद्धति

( पहला पुनरीक्षण )

---

First Reprint JUNE 1993

UDC 621.315.668.3

© BIS 1990

**BUREAU OF INDIAN STANDARDS**  
MANAK BHAVAN, 9 BHADUR SHAH ZAFAR MARG  
NEW DELHI 110002

**FOREWORD**

**This Indian Standard ( First Revision ) was adopted by the Bureau of Indian Standards on 21 December 1989, after the draft finalized by the Cement and Concrete Sectional Committee had been approved by the Civil Engineering Division Council.**

**Apart from the requirements regarding design, materials, process of manufacture, dimensions, shape, workmanship, finish, etc, acceptability of a product is determined by the results of various tests to evaluate the properties stipulated in the relevant specifications. This standard lays down the procedure for testing of reinforced concrete as well as prestressed concrete poles for street lighting, overhead electric power transmission, traction and telecommunication lines.**

**In addition to the test specified in this standard, inspection of the process of manufacture and the quality of the finished poles and other tests for the quality control of materials during manufacture, shall be carried out in accordance with the requirements of relevant specifications.**

**This standard was first published in 1966. In this revision, the test for torsional strength has been deleted since this test is not considered necessary for poles. In addition, the length of straight rope required to apply the load on the pole has been modified and the provision regarding fixing of the pole in conformity with the type of foundation to be used has been deleted. The figure illustrating the testing arrangement has also been modified in this revision.**

**The composition of the committee responsible for the preparation of this standard is given in Annex A.**

## *Indian Standard*

# CONCRETE POLES FOR OVERHEAD POWER AND TELECOMMUNICATION LINES — METHODS OF TEST

( *First Revision* )

## 1 SCOPE

**1.1** This standard covers methods of test for concrete poles for street lighting, overhead electrical power transmission, traction, telephone and telegraph lines, to evaluate the properties stipulated in the relevant specifications.

## 2 INSPECTION

**2.1** The materials to be used, processes of manufacture, and finished poles shall be open to inspection and approval by the purchaser.

## 3 TESTING FACILITIES

**3.1** Unless otherwise specified in the relevant specification or agreed to between the manufacturer and the purchaser, the purchaser or his representative shall have, at all reasonable times, free access to the place of manufacture of the poles for the purpose of examining, sampling and testing the materials and for inspecting the process of manufacture.

## 4 GENERAL PRECAUTIONS

**4.1** Unless otherwise specified in the relevant specification for the pole being tested, tests on poles shall not be carried out earlier than 28 days after the date of manufacture for poles manufactured from 33 grade ordinary Portland cement, Portland pozzolana cement or Portland slag cement and not earlier than 14 days after the date of manufacture for poles manufactured from rapid-hardening Portland cement and 43 grade and 53 grade ordinary Portland cement. The test specimens shall not have been exposed to a temperature below 4°C for 24 hours immediately preceding the test and shall be free from all visible moisture. The specimens shall be inspected and any specimen with visible flaws shall be discarded.

**4.2** If any test specimen fails because of mechanical reasons, such as, failure of testing equipment or improper specimen preparation, it shall be discarded and other specimen taken.

## 5 SELECTION OF TEST SPECIMENS

**5.1** In addition to the requirements specified in this standard, the number of test specimens and the methods of their selection shall be in accordance with specification for the type of pole being tested.

## 6 TRANSVERSE STRENGTH TEST

### 6.1 General

The pole may be tested in either horizontal or vertical position. If tested in the horizontal position, provision shall be made by suitable supports to compensate for the overhanging mass of the pole. For this purpose, the overhanging portion of the pole may be supported on a movable trolley or similar device. The frictional resistance of the supporting devices should be separately determined and deducted from the final load applied on the pole ( *see 6.2.5* ).

### 6.2 Test Equipment

**6.2.1** A schematic drawing of the test equipment and full layout for conducting tests is shown in Fig. 1. The butt of the pole shall be rigidly clamped by concrete cribs or similar rigid devices in such a manner that the clamped length of the pole shall be equal to the minimum depth of planting specified in the relevant standards. The crib shall check all longitudinal and rotational motions of the clamped portion of the pole.

**6.2.1.1** The pole shall be fixed in the crib longitudinally from butt to its ground line and then it shall be secured firmly in place. Wooden saddles with concave surfaces and other packings shall be placed around the pole to prevent injury to the butt section.

**6.2.2** To minimize vertical movement at the point of load application and to reduce the stresses due to dead mass of the pole, a suitable number of frictionless supports in the form of trollies shall be provided between the ground line and the point of application of the load. Support shall be such that any friction associated with the deflection of pole under load shall not be a significant portion of the measured load on the pole.

### 6.2.3 Loading

The load shall be applied at a point stipulated in the relevant Indian Standard by means of a suitable device, such as, a wire rope and winch placed in a direction normal to the direction of the length of the pole so that the minimum length of the straight rope under pull is not less than the length of the pole. If the loading



ultimate transverse load and held up for 2 minutes. This procedure shall be repeated until the load reaches the value of 80 percent of the ultimate transverse load and thereafter increased by 5 percent of the ultimate transverse load until failure occurs. Each time the load is applied, it shall be held for 2 minutes. The load applied shall be measured to the nearest 50 N.

### 6.3.2 Recording of Data and Measurement

6.3.2.1 Any hair cracks appearing at a stage prior to the application of design transverse load at first crack shall be measured using feeler gauges and shall be recorded. It should also be recorded whether the hair cracks, if any, produced on application of 60 percent of the minimum ultimate transverse load close up on the

removal or reduction of the test load. Recording of loads and deflections shall be made according to the requirements specified in relevant specification for the pole being tested.

6.3.2.2 The load applied to the pole at the time of failure shall be measured to the nearest 50 N ( see 6.2.5 ).

## 7 MEASUREMENT OF COVER

7.1 After completion of the transverse strength test, the sample pole shall be taken and checked for cover. The cover shall be measured to the nearest millimetre at three points, one within 1.0 m of the butt end of the pole, the second within 0.6 m from the top and the third at any intermediate point.

## ANNEX A

( Ref. Foreword )

### COMPOSITION OF THE TECHNICAL COMMITTEE

Cement and Concrete Sectional Committee, BDC 2

#### Chairman

•• Dr H. C. Visvesvaraya

#### Members

Shri K. P. Banerjee

Shri Harish N. Malani ( *Alternate* )

Shri S. K. Banerjee

Chief Engineer (BD)

Shri J.C. Basur ( *Alternate* )

Chief Engineer ( Designs )

Superintending Engineer ( S & S ) ( *Alternate* )

Chief Engineer ( Research-cum-Director )

Research Officer ( Concrete Technology ) ( *Alternate* )

Director

Joint Director ( *Alternate* )

Director

Chief Research Officer ( *Alternate* )

Director ( C&MDD-II )

Deputy Director ( C&MDD-II ) ( *Alternate* )

Shri V. K. Ghanekar

Shri S. Gopinath

Shri A. K. Gupta

Shri J. Sen Gupta

Shri P. J. Jagus

Dr A. K. Chatterjee ( *Alternate* )

Joint Director Standards (B&S)/CB-I

Joint Director Standards (B&S)/CB-II ( *Alternate* )

Shri N. G. Joshi

Shri R. L. Kapoor

Shri R. K. Saxena ( *Alternate* )

#### Representing

National Council for Cement and Building Materials, New Delhi

Larsen and Toubro Limited, Bombay

National Test House, Calcutta

Bhakra Beas Management Board, Nangal Township

Central Public Works Department, New Delhi

Irrigation Department, Government of Punjab

A P Engineering Research Laboratories, Hyderabad

Central Soil and Materials Research Station, New Delhi

Central Water Commission, New Delhi

Structural Engineering Research Centre ( CSIR ), Ghaziabad

The India Cement Limited, Madras

Hyderabad Industries Limited, Hyderabad

National Buildings Organization, New Delhi

The Associated Cement Companies Ltd, Bombay

Research, Designs and Standards Organization ( Ministry of Railways ), Lucknow

Indian Hume Pipes Co Limited, Bombay

Roads Wing ( Ministry of Transport ), Department of Surface Transport, New Delhi

*Members*

Shri G. K. Majumdar  
Shri P. N. Mehta  
Shri S. K. Mathur ( *Alternate* )  
Dr A. K. Mullick  
Shri Nirmal Singh  
Shri S. S. Miglani ( *Alternate* )  
Shri S. N. Pal  
Shri Biman Dasgupta ( *Alternate* )  
Shri R. C. Parate  
Lt-Col R. K. Singh ( *Alternate* )  
Shri H. S. Pasricha  
Shri Y. R. Phull  
Shri S. S. Seehra ( *Alternate* )  
Dr Mohan Rai  
Dr S. S. Rehsi ( *Alternate* )  
Shri A. V. Ramana  
Dr K. C. Narang ( *Alternate* )  
Shri G. Ramdas  
Dr M. Ramaiah  
Dr A. G. Madhava Rao ( *Alternate* )  
Shri A. U. Rijhsinghani  
Shri C. S. Sharma ( *Alternate* )  
Secretary  
Shri K. R. Saxena ( *Alternate* )  
Shri T. N. Subha Rao  
Shri S. A. Reddi ( *Alternate* )  
Superintending Engineer ( Designs )  
Executive Engineer ( SMD Division ) ( *Alternate* )  
Shri L. Swaroop  
Shri H. Bhattacharyya ( *Alternate* )  
Shri S. K. Guha Thakurta  
Shri S. P. Sankarnarayanan ( *Alternate* )  
Dr H. C. Visvesvaraya  
Shri D. C. Chaturvedi ( *Alternate* )  
Shri G. Raman,  
Director ( Civ Engg )

*Convener*

Dr N. Raghavendra

*Members*

Shri J. L. Bandyopadhyay  
Shri V. V. Surya Rao ( *Alternate* )  
Shri S. N. Basu  
Shri S. M. Munjal ( *Alternate* )  
Shri R. S. Bhatia  
Shri S. K. Sharma ( *Alternate* )  
Shri P. C. Chatterjee  
Shri U. N. Rath ( *Alternate* )

*Representing*

Hospital Services Consultancy Corporation ( India )  
Ltd, New Delhi  
Geological Survey of India, Calcutta  
National Council for Cement and Building Materials,  
New Delhi  
Development Commissioner for Cement Industry  
( Ministry of Industry )  
M. N. Dastur and Company Private Limited, Calcutta  
Engineer-in-Chief's Branch, Army Headquarters  
Hindustan Prefab Limited, New Delhi  
Indian Roads Congress, New Delhi ; and Central Road  
Research Institute ( CSIR ), New Delhi  
Central Road Research Institute ( CSIR ), New Delhi  
Central Building Research Institute ( CSIR ), Roorkee  
Dalmia Cement ( Bharat ) Limited, New Delhi  
Directorate General of Supplies and Disposals, New  
Delhi  
Structural Engineering Research Centre ( CSIR ),  
Madras  
Cement Corporation of India, New Delhi  
Central Board of Irrigation and Power, New Delhi  
Gammon India Limited, Bombay  
Public Works Department, Government of Tamil Nadu  
Orissa Cement Limited, New Delhi  
Gannon Dunkerley & Co Ltd, Bombay  
The Institution of Engineers ( India ), Calcutta  
Director General, BIS ( *Ex-officio Member* )

*Secretary*

Shri N. C. Bandyopadhyay  
Joint Director ( Civ Engg ), BIS  
Concrete Poles Subcommittee, CED 2 : 12

National Council for Cement and Building Materials,  
New Delhi  
Indian Posts and Telegraph Department, Jabalpur  
Directorate General of Supplies and Disposals, New  
Delhi  
Punjab State Electricity Board, Patiala  
Orissa Cement Ltd, Rajgangpur

*Members*

Director ( RE )

Deputy Director ( RE ) ( *Alternate* )

Shri G. L. Dua

Shri P. D. Gaikwad ( *Alternate* )

Joint Director Standards (B&S) CB-II

Deputy Director (Civil II) ( *Alternate* )

Shri N. G. Joshi

Shri S. K. Naithani

Shri Subhash Garg ( *Alternate* )

Shri H. S. Pasricha

Shri A. K. Chadha ( *Alternate* )

Dr C. Rajkumar

Shri R. Sampat Kumaram

Shri Ramesh Chander ( *Alternate* )

Shri A. V. Talati

Shri H. C. Shah ( *Alternate* )

Shri T. G. Tepan

Shri R. B. Joshi ( *Alternate* )

Shri S. Theagarajan

Shri Lakshminarasimhan ( *Alternate* )

Prof P. C. Varghese

Shri K. George ( *Alternate* )

Dr B. Venkateswarlu

*Representing*

Central Electricity Authority, Rural Electrification  
Directorate, New Delhi

Rural Electrification Corporation Ltd, New Delhi

Research, Designs and Standards Organization,  
Lucknow

The Indian Hume Pipe Co Ltd, Bombay

Engineer-in-Chief's Branch, Army Headquarters,  
New Delhi

Hindustan Prefab Ltd, New Delhi

National Council for Cement and Building Materials,  
New Delhi

Delhi Electric Supply Undertaking, New Delhi

The Steel Pipe & Fabrication Works, Vadodara

Maharashtra State Electricity Board, Bombay

Tamil Nadu Electricity Board, Madras

The Concrete Products and Construction Co,  
Poonamallee (TN)

Structural Engineering Research Centre (CSIR),  
Madras

**Standard Mark**

The use of the Standard Mark is governed by the provisions of the *Bureau of Indian Standards Act, 1986* and the Rules and Regulations made thereunder. The Standard Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well defined system of inspection, testing and quality control which is devised and supervised by BIS and operated by the producer. Standard marked products are also continuously checked by BIS for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the Standard Mark may be granted to manufacturers or producers may be obtained from the Bureau of Indian Standards.

## Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act, 1986* to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

### Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

### Revision of Indian Standards

Indian Standards are reviewed periodically and revised, when necessary and amendments, if any, are issued from time to time. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition. Comments on this Indian Standard may be sent to BIS giving the following reference :

Doc : No. CED 2 ( 4115 )

### Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

## BUREAU OF INDIAN STANDARDS

### Headquarters :

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002  
Telephones : 331 01 31, 331 13 75

Telegrams : Manaksanstha  
( Common to all Offices )

### Regional Offices :

Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg  
NEW DELHI 110002

Telephone

{ 331 01 31  
{ 331 13 75

Eastern : 1/14 C.I.T. Scheme VII M, V.I.P. Road, Maniktola  
CALCUTTA 700054

37 86 62

Northern : SCO 445-446, Sector 35-C, CHANDIGARH 160036

2 18 43

Southern : C.I.T. Campus, IV Cross Road, MADRAS 600113

41 29 16

Western : Manakalaya, E9 MIDC, Marol, Andheri ( East )  
BOMBAY 400093

6 32 92 95

Branches : AHMADABAD. BANGALORE. BHOPAL. BHUBANESHWAR.  
COIMBATORE, FARIDABAD, GHAZIABAD, GUWAHATI.  
HYDERABAD. JAIPUR. KANPUR. PATNA. TRIVANDRUM.