

IS : 3456 - 1966
(Reaffirmed 1993)

Indian Standard
METHOD FOR
DETERMINATION OF WATER SOLUBLE
MATTER OF TEXTILE MATERIALS
(Third Reprint MAY 1997)

UDC 677.01 : 543.831

© Copyright 1966

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

Indian Standard

METHOD FOR
DETERMINATION OF WATER SOLUBLE
MATTER OF TEXTILE MATERIALS

Textile Chemistry Sectional Committee, TDC 5

<i>Chairman</i>	<i>Representing</i>
DR P. C. MEHTA	The Ahmedabad Textile Industry's Research Association, Ahmedabad
<i>Members</i>	
SHRI K. L. AHUJA	Directorate of Industries, Government of Punjab
SHRI K. D. BAHADURJI	Textile Auxiliaries Manufacturers' Association, Bombay
SHRI J. N. BHATT	Association of Merchants & Manufacturers of Textile Stores & Machinery, India, Bombay
SHRI K. S. BHUJANG	Office of the Textile Commissioner, Bombay
DR I. B. CHAKRAVERTI	Indian Jute Mills Association Research Institute, Calcutta
SHRI R. C. DASGUPTA	National Test House, Calcutta
DIRECTOR OF HANDLOOMS	Government of Madras
SHRI R. SUBRAMANIAN (<i>Alternate</i>)	
SHRI S. K. DUTTA	Ahmedabad Manufacturing & Calico Printing Co Ltd, Ahmedabad
SHRI GUNVANT MANGALDAS	Ahmedabad Millowners' Association, Ahmedabad
DR V. P. KULKARNI	All India Handloom Board, Bombay
SHRI L. G. MAKHIJANI	Indian Rope Manufacturers' Association, Calcutta
SHRI A. K. GHOSE (<i>Alternate</i>)	
SHRI S. B. MEHTA	The Bombay Textile Research Association, Bombay
SHRI S. S. MEHTA	I.C.I. (India) Private Ltd, Calcutta
SHRI V. J. VAISHNAV (<i>Alternate</i>)	
DR S. H. MHATRE	The Bangalore Woollen, Cotton & Silk Mills Co Ltd, Bangalore; and the Buckingham & Carnatic Company Limited, Madras
SHRI S. M. MISTRY	Association of Merchants & Manufacturers of Textile Stores & Machinery, India, Bombay
DR C. N. K. MURTHY	Ministry of Defence (DGI)
SHRI C. L. GUPTA (<i>Alternate</i>)	
SHRI P. S. NADKARNI	Ministry of Defence (DGI)
DR V. N. NIGAM	Ministry of Defence (R & D)
SHRI N. D. BHANDARI (<i>Alternate</i>)	
DR M. V. NIMKAR	The Millowners' Association, Bombay
SHRI I. P. PAREKH	The Silk & Art Silk Mills' Research Association, Bombay
DR D. V. PARIKH	The Bombay Textile Research Association, Bombay
SHRI J. G. PARIKH	Silk & Art Silk Mills' Association, Ltd, Bombay

(Continued on page 2)

IS : 3456 - 1966

(Continued from page 1)

Members

SHRI GORDHANBHAI H. PATEL
SHRI I. L. PATEL

SHRI Y. G. PATHAK
REPRESENTATIVE
SHRI JAMNADAS K. SHAH
SHRI R. C. SHAH

SHRI G. V. SHIRODKAR
SHRI T. BALAKRISHNAN,
Deputy Director (Tex)

Representing

Shri Dinesh Mills Ltd, Baroda
Inspection Wing, Directorate General of Supplies & Disposals
The Textile Processors' Association (India), Bombay
Shri Ram Institute for Industrial Research, Delhi
The Raipur Manufacturing Co Ltd, Ahmedabad
The Ahmedabad Textile Industry's Research Association, Ahmedabad
Delhi Cloth & General Mills Co Ltd, Delhi
Director General, ISI (*Ex-officio Member*)

Secretary

SHRI G. S. ABHYANKAR
Assistant Director (Tex), ISI

Undyed Textile Materials Subcommittee, TDC 5 : 2

Convener

SHRI R. C. SHAH
The Ahmedabad Textile Industry's Research Association, Ahmedabad

Members

SHRI G. G. KULKARNI (*Alternate to*
Shri R. C. Shah)

SHRI K. L. AHUJA
DR (MISS) M. D. BHAVSAR

SHRI R. J. CHIKTE

SHRI C. L. GUPTA
SHRI B. K. KEDIA
SHRI K. MANIVANNAN
DR V. N. NIGAM

SHRI N. D. BHANDARI (*Alternate*)
DR D. V. PARIKH
SHRI JAMNADAS K. SHAH

Directorate of Industries, Government of Punjab
The Silk & Art Silk Mills Research Association, Bombay
The Khatau Makanji Spinning & Weaving Co Ltd, Bombay
Ministry of Defence (DGI)
The Raymond Woollen Mills Ltd, Bombay
Shri Ram Institute for Industrial Research, Delhi
Ministry of Defence (R & D)
The Bombay Textile Research Association, Bombay
Raipur Manufacturing Co Ltd, Ahmedabad

Indian Standard
METHOD FOR
DETERMINATION OF WATER SOLUBLE
MATTER OF TEXTILE MATERIALS

0. FOREWORD

0.1 This Indian Standard was adopted by the Indian Standards Institution on 11 May 1966, after the draft finalized by the Textile Chemistry Sectional Committee had been approved by the Textile Division Council.

0.2 In textile industry textile materials undergo various treatments, in the course of which extraneous matter of various types, such as sizing or finishing material, water soluble matter is gathered by or added to the original textile material. An Indian Standard for determining size or finish, ash and fatty matter in cotton textile materials has already been published. The water soluble matter if present beyond certain limits in the textile materials adversely affects its quality.

0.3 In reporting the result of a test or analysis made in accordance with this standard, if the final value, observed or calculated, is to be rounded off, it shall be done in accordance with IS : 2-1960*.

1. SCOPE

1.1 This standard prescribes a method for determination of water soluble matter of textile materials.

2. SAMPLING

2.1 Sampling for Fibre and Yarn

2.1.1 *Lot (Fibre or Yarn)* — The quantity of fibre or yarn from the same source shall constitute a lot. If the lot contains more than 200 kg of fibre or yarn, it shall be divided in sub-lots each weighing 200 kg or less.

2.1.2 From a sub-lot 15 increments each approximately weighing 10 g shall be taken from different parts so that a representative sample is obtained. All the increments thus collected shall be thoroughly mixed. This shall constitute the test sample.

*Rules for rounding off numerical values (*revised*).

2.2 Sampling for Fabrics

2.2.1 Lot (Fabric) — The quantity of fabrics manufactured under relatively uniform conditions shall constitute a lot.

2.2.2 The number of pieces to be selected from a lot shall be in accordance with Table 1. The pieces thus selected shall constitute the gross sample.

TABLE 1 SAMPLE SIZE

LOT SIZE (1)	SAMPLE SIZE (2)
Up to 100	3
101 „ 300	4
301 „ 500	5
501 and above	7

2.2.3 From each piece in the gross sample about 25 g of fabric shall be taken out from at least two different parts. The parts shall then be cut into further smaller pieces and thoroughly mixed. The pieces thus collected shall constitute the test sample.

3. TEST SPECIMENS

3.1 From the test sample, cut out at least two test specimens each weighing about 10 g. Cut the test specimens into small pieces.

NOTE — If the sample under analysis is loose fibre, take about 5 g of the test specimen.

4. CONDITIONING OF TEST SPECIMENS

4.1 Prior to test, the test specimens shall be conditioned for 24 hours to moisture equilibrium in a standard atmosphere at 65 ± 2 percent relative humidity and $27 \pm 2^\circ\text{C}$ temperature (see IS: 196-1966*). However, in case of fabrics which weigh more than 270 g/m^2 , the test specimens shall be conditioned for 48 hours.

5. APPARATUS

5.1 Flat-Bottom Flasks — of suitable capacity with a glass stopper incorporating a stop-cock.

NOTE — The flasks that are used for the preparation of the extract should not be used for any other purpose.

5.2 Water Cooled Condensers

*Atmospheric conditions for testing (revised).

6. REAGENT

6.1 Distilled Water — conforming to IS : 1070-1960*.

7. PROCEDURE

7.1 Condition the test specimens to moisture equilibrium in the standard atmosphere (*see 4*) and weigh accurately each test specimen.

7.2 Put a test specimen in the flask and add sufficient amount of water to it to make a liquor to material ratio of 20 : 1 (*see Note 1*). Connect the flask to the condenser and bring rapidly to the boil and continue to boil the liquor gently for 60 minutes. Disconnect and remove the flask while the liquor is still boiling and close it immediately with the glass stopper fitted with stop-cock.

Rapidly cool the flask to room temperature ($27^{\circ} \pm 2^{\circ}\text{C}$). Do not remove or open the tap until ready for filtration. Reject any extract where the flask is not under vacuum at the time of opening. Filter the extract and wash the residue with small amount of water. Take the filtrate and washings in a tared vessel and evaporate the extract to dryness (*see Note 2*). Dry the residue to constant weight at 105° to 110°C .

NOTE 1 — If the test specimen is wool, the liquor to material ratio should be 50 : 1.

NOTE 2 — The filtrate and washings may be diluted to a suitable volume and a measured amount of the solution may be evaporated for estimation.

7.3 Calculate the water soluble matter as a percentage of the conditioned weight of the specimen by the following formula:

$$P = \frac{W_2}{W_1} \times 100$$

where

P = percentage of water soluble matter;

W_2 = weight, in g, of the residue (*see 7.2*); and

W_1 = weight, in g, of the conditioned test specimen (*see 7.1*).

7.4 Repeat the test as given in **7.2** with the remaining test specimen(s) and calculate the percentage of water soluble matter in each test specimen.

8. REPORT

8.1 Calculate the average of the values obtained as in **7.3** and **7.4**, and report it as the percentage of water soluble matter of the textiles.

*Specification for water, distilled quality (*revised*).

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

Telephones: 323 0131, 323 3375, 323 9402

Fax : 91 11 3234062, 91 11 3239399, 91 11 3239382

Telegrams : Manaksar
(Common to all Off

Central Laboratory:

Plot No. 20/9, Site IV, Sahibabad Industrial Area, SAHIBABAD 201010

Telep
8-77 0

Regional Offices:

Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002 323 7
*Eastern : 1/14 CIT Scheme VII M, V.I.P. Road, Maniktola, CALCUTTA 700054 337 8
Northern : SCO 335-336, Sector 34-A, CHANDIGARH 160022 60 3
Southern : C.I.T. Campus, IV Cross Road, CHENNAI 600113 235 2
†Western : Manakalaya, E9 Behind Marol Telephone Exchange, Andhari (East), 832 9.
MUMBAI 400093

Branch Offices:

'Pushpak', Nurmohamed Shaikh Marg, Khanpur, AHMEDABAD 380001 550 1;
‡Peenya Industrial Area, 1st Stage, Bangalore - Tumkur Road, 839 4;
BANGALORE 560058
Gangotri Complex, 5th Floor, Bhadbhada Road, T. T. Nagar, BHOPAL 462003 55 40
Plot No. 62-63, Unit VI, Ganga Nagar, BHUBANESHWAR 751001 40 36
Kalaikathir Buildings, 670 Avinashi Road, COIMBATORE 641037 21 01
Plot No. 43, Sector 16 A, Mathura Road, FARIDABAD 121001 8-28 88
Savitri Complex, 116 G. T. Road, GHAZIABAD 201001 8-71 19
53/5 Ward No. 29, R. G. Barua Road, 5th By-lane, GUWAHATI 781003 54 11
5-8-58C, L. N. Gupta Marg, Nampally Station Road, HYDERABAD 500001 20 10
E-52, Chitaranjan Marg, C-Scheme, JAIPUR 302001 37 29
117/418 B, Sarvodaya Nagar, KANPUR 208005 21 68
Seth Bhawan, 2nd Floor, Behind Leela Cinema, Naval Kishore Road, 23 89
LUCKNOW 226001
Patliputra Industrial Estate, PATNA 800013 26 23
T. C. No. 14/1421, University P. O. Palayam, 6 21
THIRUVANANTHAPURAM 695034
NIT Building, Second Floor, Gokulpat Market, NAGPUR 440010 52 51
Institution of Engineers (India) Building, 1332 Shivaji Nagar, PUNE 411005 32 36
*Sales Office is at 5 Chowringhee Approach, P. O. Princep Street, 27 10
CALCUTTA 700072
†Sales Office is at Novelty Chambers, Grant Road, MUMBAI 400007 309 65
‡Sales Office is at 'F' Block, Unity Building, Narashimaraja Square, 222 39
BANGALORE 560002