

IS : 6932 ( Part II ) - 1973

*Indian Standard*

**METHODS OF TESTS FOR BUILDING LIMES**

**PART II DETERMINATION OF CARBON DIOXIDE  
CONTENT**

( Third Reprint APRIL 1993 )

UDC 691.51 : 543 [ 546.264 ]

© *Copyright* 1974

**BUREAU OF INDIAN STANDARDS**  
**MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG**  
**NEW DELHI 110002**

## *Indian Standard*

### METHODS OF TESTS FOR BUILDING LIMES

#### PART II DETERMINATION OF CARBON DIOXIDE CONTENT

### 0. FOREWORD

**0.1** This Indian Standard ( Part II ) was adopted by the Indian Standards Institution on 22 March 1973, after the draft finalized by the Building Limes Sectional Committee had been approved by the Civil Engineering Division Council.

**0.2** Hitherto, methods of tests for assessing qualitative requirements of building limes were included in IS : 712-1964. For facilitating the use of these tests it has been decided to print these tests as different parts of a separate Indian Standard. This part covers determination of carbon dioxide content of building limes.

**0.3** In reporting the results of a test or analysis made in accordance with this standard, if the final value, observed or calculated, is to be rounded off, it shall be done in accordance with IS : 2-1960\*.

---

### 1. SCOPE

**1.1** This standard ( Part II ) covers method of test for determination of carbon dioxide content of building lime.

### 2. GENERAL

**2.1 Preparation of the Sample** — The sample for carrying out this test shall be prepared in accordance with **7.2** of IS : 712-1973†.

**2.2** The distilled water ( *see* IS : 1070-1970‡ ) shall be used where use of water as a reagent is intended.

---

\*Rules for rounding of numerical values ( *revised* ).

†Specification for building limes ( *second revision* ).

‡Specification for water, distilled quality ( *revised* ). ( *Since revised* ).

### 3. DETERMINATION OF CARBON DIOXIDE CONTENT

#### 3.1 Apparatus and Reagents

**3.1.1** A suitable form of apparatus is shown in Fig. 1. The system consists of a U-tube *A* with anhydrous granulated calcium chloride and another U-tube *B* with soda asbestos, funnel *C* with a glass stopcock *S* and a bent inlet glass tube ( projecting below the acid level ) is used to introduce hydrochloric acid into the generating flask *D*. Condenser *E* condenses most of the water and hydrochloric acid. The U-tube *F* contains zinc pallets to react with residual acid, if any. Bubbler *G* contains concentrated sulphuric acid to absorb moisture. The U-tube *H*<sub>1</sub> contains pumice stone, impregnated with anhydrous copper sulphate to remove traces of hydrogen sulphide. Pumice stone is prepared by crushing it to approximately 5 mm size, shifting it free from dust and then transferring 60 g of it to a casserole, it is then covered with a concentrated solution of 30 to 35 g of copper sulphate and then evaporated to dryness while stirring constantly. It is then heated for 3 to 4 hours at 150 to 160°C, cooled in a desiccator and preserved in a glass-stoppered bottle. U-tube *H* contains anhydrous granulated calcium chloride in one limb and anhydrous magnesium perchlorate in the other to remove the last traces of moisture. U-tubes *J*<sub>1</sub> and *J* contain both soda asbestos and anhydrous magnesium perchlorate in each limb to absorb carbon dioxide. U-tube *K* contains anhydrous granulated calcium chloride and anhydrous magnesium perchlorate in each limb to protect the end of the train against moisture. U-tubes are suspended from a cross bar *N*. Two retort stands *L* and *M* carry the cross bar *N*. All joints are made of stout-walled rubber tubing with the ends of the glass tubes touching each other. Means are provided to pass air through the system either under pressure or by suction.

**3.1.2 Dilute Hydrochloric Acid** — 1 : 4 ( *v/v* ). It shall be prepared by diluting hydrochloric acid ( sp gr 1.16 and conforming to IS : 265-1962\* ) four times its volume with water.

**3.2 Procedure** — Accurately weigh about 2.5 g of the sample, transfer it into the flask *D* and add 20 to 40 ml of distilled water. Insert the glass stopper carrying the funnel arrangement and condenser and make sure that the apparatus is air-tight. Pass air through the system until the carbon dioxide absorption tubes *J*<sub>1</sub> and *J* attain constant mass. Close the stopcock (*S* and reconnect in the system the weighed carbon dioxide absorption tubes *J*<sub>1</sub> and *J*). Introduce 40 ml of hydrochloric acid into the flask *D* through funnel *C* and heat the flask carefully so that the gases pass through the sulphuric acid bubbler at a moderate rate. Allow the contents of the flask to boil after about 30 to 40 minutes. After 2 to 3 minutes of boiling, remove the flame and connect the flask to scrubbers *A* and *B* by means of stopcock *S* and pass air through the system for 20 minutes at a moderate rate. Keep

\*Specification for hydrochloric acid ( revised ).




FIG. 1 ASSEMBLY OF APPARATUS FOR DETERMINATION OF CARBON DIOXIDE IN LIME

## **IS : 6932 ( Part II ) - 1973**

the absorption tubes  $\mathcal{J}_1$  and  $\mathcal{J}$  at room temperature for 30 minutes and then weigh. The increase in mass denotes the carbon dioxide content in the sample.

**3.3 Report of Test Results** — The carbon dioxide content shall be reported as a percentage of mass of the sample taken.

# BUREAU OF INDIAN STANDARDS

**Headquarters:**

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

Telephones : 331 01 31, 331 13 75

Telegrams : Manaksanatha  
( Common to all offices )

**Regional Offices:**

	<i>Telephones</i>
<b>Central</b> : Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI-110002	[ 331 01 31 331 13 75
* <b>Eastern</b> : 1/14 C.I.T. Scheme VII M, V. I. P. Road, Maniktola, CALCUTTA 700054	36 24 99
<b>Northern</b> : SCO 445-446, Sector 35-C, CHANDIGARH 160038	[ 2 18 43 3 18 41
<b>Southern</b> : C. I. T. Campus, MADRAS 600113	{ 41 24 42 41 25 19 41 29 16
† <b>Western</b> : Manakalaya, E9 MIDC, Marol, Andheri (East), BOMBAY 400093	6 32 92 95

**Branch Offices:**

'Pushpak' Nurmohamed Shaikh Marg, Khanpur, AHMEDABAD 380001	[ 2 63 48 2 63 49
‡Peenya Industrial Area, 1st Stage, Bangalore Tumkur Road BANGALORE 560058	[ 38 49 55 38 49 56
Gangotri Complex, 5th Floor, Bhadbhada Road, T. T. Nagar, BHOPAL 462003	6 67 16
Plot No. 82/83, Lewis Road, BHUBANESHWAR 751002	5 36 27
53/5, Ward No. 29, R. G. Barua Road, 5th Byelane, GUWAHATI 781003	3 31 77
5-8-56C L. N. Gupta Marg ( Nampally Station Road ), HYDERABAD 500001	23 10 83
R14 Yudhister Marg, C Scheme, JAIPUR 302005	[ 6 34 71 6 98 32
117/418 B Sarvodaya Nagar, KANPUR 208005	[ 21 68 76 21 82 92
Patliputra Industrial Estate, PATNA 800013	6 23 05
T.C. No. 14/1421, University P.O., Palayan TRIVANDRUM 695035	[ 6 21 04 6 21 17
<b>Inspection Office (With Sale Point) :</b>	
Pushpanjali, 1st Floor, 205-A West High Court Road, Shankar Nagar Square, NAGPUR 440010	2 51 71
Institution of Engineers ( India ) Building, 1332 Shivaji Nagar, PUNE 411005	5 24 35

\*Sales Office in Calcutta is at 5 Chowringhee Approach, P.O. Princep Street, Calcutta 700072 27 68 00

†Sales Office in Bombay is at Novelty Chambers, Grant Road, Bombay 400007 89 65 28

‡Sales Office in Bangalore is at Unity Building, Narasimharaja Square Bangalore 560002 22 36 71