


# Structural Design of Bridge Khadi Khad, Pathankot



All unit in meter(m)

## DECK SLAB

Thickness of slab = 0.25



Wearing Coat = 0.1 m

Grade of Concrete = M30

Dead Load = 6.25 KN/ m<sup>2</sup>

DL of Wearing Coat = 2.2 KN/ m<sup>2</sup>

Total DL = 8.5 KN/ m<sup>2</sup>



## Class AA Tracked Vehicle

Wheel Division:-

$$l = 0.85 \text{ m}$$

$$b = 3.6 \text{ m}$$

$$u = 0.85 + 0.2 = 1.05 \text{ m} \quad v = 3.6 + 0.2 = 3.8 \text{ m}$$

## One Way Slab:-

Impact factor = 0.25 m

$$\text{Wheel Load / m} = 350/0.380 = 92 \text{ KN/ m} \quad \text{DL} = 8.5 \text{ KN/ m}$$

$$\text{B.M} = 8.5 \times 3^2/8 + (92/2 \times 3/2 - 92/2 \times 1.05/4) \times 1.25 = 9.56 + 56.92 \times 1.25 = 80.7 \text{ KN-m}$$

## Continuity Effect:-

$$\text{B.M at support} = 9.56 \times 8/10 + 56.92 \times 4/8 \times 1.25 = 43.25 \text{ KN-m}$$


$$\text{S.F} = 8.5 \times 3/2 + 92 \times 1.05/2 \times 1.25 = 73.13 \text{ KN-m}$$

$$\text{Mu} = 64.87 \text{ KN-m}$$

$$\text{Vu} = 109.7 \text{ KN}$$

Provide  $\phi 12 @ 100\text{mm c/c}$  main(cross)

Provide  $\phi 10 @ 100\text{mm c/c}$  distance (long.)



## CANTILEVER SLAB

$$b_e = 1.2x + b_w = 1.2 \times 0.2 + (0.25 + 2 \times 0.1) = 0.69 \text{ m}$$

$$\text{Live Load/m} = 57 \times 1.5/0.69$$

$$\text{Maximum moment due to L.L} = 123.9 \times 0.2 + 5 \times 1.125 \times 0.763 = 29.07 \text{ KNm}$$

$$\text{Moment due to D.L} = 1.7 \times 1.4 + 0.55 \times 0.55 \times 2 \times 25 + 0.26 \times 25 \times 2.275^2/2 + 0.1 \times 0.6 \times 0.3 \times 20$$

$$= 2.436 + 15.13 + 16.82 + 0.36 = 34.746 \text{ KN-m}$$

$$\text{Total B.M} = 29.07 + 34.75 = 63.82 \text{ KN-m}$$

$$\text{S.F} = (123.9 \times 0.45) + 5 \times 1.125 + (7.6 + 14.8 + 1.8) = 83.6 \text{ KN}$$

$$\text{Mu} = 95.73 \text{ KN-m}$$

$$\text{Vu} = 128.4 \text{ KN-m}$$

$$\text{Mu/bd}^2 = 95.73 \times 10^6 / 1000 \times 300^2 = 1.064$$

$$\text{Pt} = 0.265\%$$

$$\text{Ast} = 7.95 \text{ cm}^2$$

Provide  $\phi 12 @ 100 \text{ c/c main}$

Provide  $\phi 10 @ 150 \text{ c/c dist.}$

### Longitudinal Girders ( Intermediate Girders):-

B.M due to dead load (Intermediate Girder/m length)


Sr No.	Item	Details	Weight (KN)
1.	Wearing Coat	3.0 x 0.1 x 22	66
2.	Deck Slab	3.0 x 0.25 x 25	18.75
3.	T Beam	0.4 x 2.5 x 25	25
4.	Cross Beams	(3.0 x 2.0 x 25 x 0.5)/41	2.57(say) = 52.92 KN/m $\approx 53 \text{ KN/m}$

$$\text{Maximum B.M due to DL} = 50 \times 41^2/8 = 10506 \text{ KN-m}$$

$$\text{Maximum S.F due to DL} = 50 \times 41/2 = 1025 \text{ KN}$$

### D.L in end Girder/m length:-

Sr No.	Item	Details	Weight (KN)
1.	Wearing Coat	0.75 x 0.1 x 22	4.96
2.	Deck Slab	0.263 x 2.425 x 25	15.94
3.	End beam	0.55 x 0.55 x 25	7.56
4.	Parapet	0.2 x 1 x 25	5
5.	Front Path	0.3 x 1.125 x 20	6.75
6.	Self weight	0.4 x 2.5 x 25	25
7.	Cross Beam		1.29 (say)
			= 66.5 KN/m $\approx 67 \text{ KN/m}$



### Live Load Calculations:-

$$\text{Impact Load} = 4.5 / (6 + 41) = 0.1$$

$$\text{Max. Wheel Load}(W) = \text{Axle Load} / 2 \times 1.1 \times 1.52 = \text{Axle Load} \times 0.836$$

### Seismic analysis:

$$T = 2.0 \sqrt{D / 1000F}$$

$$D = DL + 0.2LL = 4980 + 0.2 \times (365 \times 3) = 5199 \text{ kN}$$

$$\text{Here } F = D \times 6EI / L^3$$

$$= (1) \times 6 \times 31.22 \times 1.083 \times 10^{12} / 5000^3 = 1623 \text{ kN}$$

$$T = 2.0 \sqrt{5199 / 1000 \times 1623} = 0.11 \text{ sec}$$


$$S_a / g = 2.5$$

$$A_h = Z / 2 \times 2 \times I \times S_a / g = 0.24 / 2 \times (1.2 \times 2.5) = 0.25$$


$$H = 0.25 \times 1244 = 311 \text{ kN}$$

$$M = 311 \times 5 = 1555 \text{ kN}$$

Total moment = 1555 + 869.3 = 2424 kN m



All units in Meter(m)



Loads on Abutment

### Forces and moments about base/m length of Abutment :

Sr No.	Details	Vertical Forces (KN)	Horizontal Forces(KN)	Lever Arm (m)	Moment About 0 KNm
1.	Dead Load For Structure	$1660 * 3 / 7.5 = 664$	--	0.15	99.6
2.	Active Earth Pressure	---	45	2.23	100.35
3.	Horizontal Force Due to live load Surcharge	---	80	3.35	268
4.	Vertival force due to Live load surcharge	75	---	1.85	139
5.	Self weight 1 2 3 4 <b>Total:</b>	125 -- 13 -- <b>138 KN</b>	---	0 -- -0.35 --	0 -- -4.55 --
6.	Live load for structure	$365 * 3 / 7.5 = 146$	--	0.15	219
7.	Horizontal Bending moment	---	15	5.71	86
	Total	1023	170		907.4 kNm

Total vertical load at base =  $1023 * 7.5 = 7673$  KN

Total horizontal load at base =  $170 * 7.5 = 1275$  kN

Total bending moment at base =  $907.4 * 7.5 = 6806$  KNm

## Design of Abutment :-

### 1.5 (DL+LL):

$$M = 907.4 \text{ KN-m}$$

$$M_u = 1361 \text{ KN-m}$$

$$V = 170 \text{ KN}$$

$$V_u = 255 \text{ KN}$$

$$M_u/bd^2 = 1361 \times 10^6 / (1000 \times 950^2) = 1.51$$

$$P_t = 0.37\%$$

### 1.2 (DL+LL+EQ):

$$M = 2424/7.5 = 323.24 \text{ KN-m}$$

$$M_u = 388 \text{ KN-m}$$

$$V = 170 + 311/7.5 = 211 \text{ KN}$$

$$V_u = 254 \text{ KN}$$

$$M_u/bd^2 = 388 \times 10^6 / (1000 \times 950^2) = 0.43$$

$$A_{st} = 3561 \text{ mm}^2$$

$$\tau_u = 276 \times 10^3 / 1000 \times 950 = 0.29 \text{ N/mm}^2$$

$$\tau_c = 0.36 \text{ N/mm}^2 \text{ SAFE}$$

Provide 20Ø @ 80 c/c main steel on Earth force

Provide 20Ø @ 160 c/c main steel on Free force

Provide 12Ø @ 100 c/c Distribution steel

## MEAN SCOUR DEPTH

$$\text{Clear waterway} = 39.8 \text{ m}$$

$$\text{Silt factor}(f) = 2.96$$

$$Q = 454 \text{ cumec}$$

$$\text{Unit discharge}(q) = 454/39.8 = 11.41 \text{ cumec/m width}$$



$$\text{Mean Scour Depth} = 1.34(q^2/f)^{1/3} = 4.56\text{m}$$

$$\text{Max. Scour Depth} = 2 \times 4.71 = 9.12\text{m}$$

$$\text{Grip Length} = \frac{1}{3}(\text{max scour depth} = 3.04\text{ m (provide} = 5.78\text{m)})$$

$$\text{Depth of Foundation below HFL} = 9.12 + 3.04 = 12.16\text{ m (provide} = 15.2\text{m)}$$

$$\text{Depth of foundation Below} = 12.16 - 2.2 = 9.96\text{m (provide} = 13\text{m)}$$

$$M = (3843 - 1190) \times 7.5 = 19898\text{ KN-m}$$

$$V = 1098 \times 7.5 = 8235\text{ KN}$$

$$H = 289 \times 7.5 = 2168\text{ KN}$$

## DESIGN OF WELL

Min thickness of stiening = 500 mm

$$\text{Thickness} = h = Kd\sqrt{L} = 0.030 \times 6.5 \times \sqrt{13} = 0.703\text{ m (Provide 750mm)}$$

## Bearing Pressure

### Self Weight of well :

$$\text{Area of cross section of well} = \pi/4(6.5^2 - 5^2) + 6.5 \times 0.75 \times 2 + 0.75 \times 5.2 = 27.2\text{ m}^2$$

$$\text{Internal area of well} = 75.43 - 27.2 = 48.23\text{ m}^2$$

$$\text{Area of base} = \pi/4 \times 6.5^2 + 6.5 \times 6.5 = 75.43\text{m}^2$$

$$\text{Weight of well} = (27.2 \times 13 \times 25) + (48.23 \times 11 \times 18) + 48.23 \times 2 \times 2 \times 25 = 23386\text{ KN}$$

$$\text{Weight of soil on cap} = (13 + 6.5)/2 \times 6.7 \times 3.5 \times 18 = 3904\text{ KN}$$

$$\text{Total load at base} = 7673 + 23386 + 3904 = 34963\text{ KN}$$

$$\text{Bearing pressure} = 34963/75.73 = 461.7\text{ KN/m}^2 \text{ (Neglecting friction)}$$

## Reinforcement

Vertical reinforcement ( 0.12%)

$$= .12/100 \times \pi/4 \times 23.78 = .023\text{ m}^2 = 230\text{ cm}^2$$

Provide 12  $\phi$ bars @ 100 c/c on each face vertically

Horizontal reinforcement (0.2%)

Provide 12Ø @100c/c on each face

## Bottom Plug

Thickness of bottom plug is

$$t^2 = 1.18 \times r^2 q / f_c = 1.18 \times 3.25^2 \times 400 / 7000 = .71 \text{ m say } 800 \text{ mm}$$

## Check For Section adopted

Distance of zero shear ( max. BM) for scour level

$$X = \sqrt{(2FH / -Ka) / \gamma b (Kp \beta)}$$

Assuming  $\theta = 30^\circ$ ,  $\delta\theta / 2 = 15^\circ$ ,  $\theta^\circ = 45$

$$Ka = (\cos\theta / (\sqrt{\cos\delta} + \sqrt{\sin(\theta + \delta)} \times \sin\theta))^2$$

$$Kp = (\cos\theta / (\sqrt{\cos\delta} - \sin(\theta + \delta)) \times \sin\theta)^2$$

$$Ka = .30, Kp = 5.0$$

$$\text{Therefore } x^2 = 2 * 2 * 1275 / (9.5(5-0.3)6.5) = 17.57 \text{ X} = 4.19\text{m}$$

$$\text{Max BM is } M_{\max} = M_o + 2/3 Hx$$

$$\text{Permissible tilt} = 50 \text{ mm}$$

$$\text{Tilt at scour level} = 50 \times 3.14 / 15.5 = 10.13 \text{ mm} = 11\text{mm}$$

$$\text{Moment to tilt} = 0.012 \times 27226 = 327 \text{ KN-m}$$

$$M_{\max} = 327 + 2/3 \times 1275 \times 4.19 = 3888 \text{ KN-m}$$

$$\text{MOI} = \pi/64 \times 5(.2^4)6 + (.65^4 \cdot 5 \cdot 6.5^3 / 12 - 6.5 \cdot 5.2^3 / 12) = 124.32 \text{ m}^4$$

## Max Stress in steining

$$\sigma_{\max} = 34963 / 23.78 + (3888 / 124.32 \times 3.25)$$

$$1470 \pm 103 \text{ KN/m}^2 = 1573 \text{ KN} / \text{m}^2 = 1.6 \text{ N/mm}^2 < 6.0 \text{ N/mm}^2 \text{ (M25)}$$

$$V = 5768 \text{ KN}, H = 1275 \text{ KN}, M = 6518 \text{ KN}$$


$$\text{Upward Pressure} = \mu P ;$$

$$P = \gamma (Kp - Ka) L D^2 / 6$$


$$P = 9.5(5-0.3) 13 \cdot 5.78^2 / 6 = 3232 \text{ kN}$$

$$\text{Total vertical load} = (34963 - 3232) = 31731 \text{ KN}$$

$$\text{Bearing pressure} = 31731 / 75.43 = 420.7 \text{ KN/m}^2$$



## Design of well cap



$$L = 5.85 \text{ m}$$

$$b = 1.54 \text{ m}$$

$$a = 4.31 \text{ m}$$

$$c = 2.16 \text{ m}$$

(At  $x = b$ )

$$M = V_e c_b/L + M_b/L + V_a/L$$

$$S.F = V_e c/L + M/L + V_a$$

$$M = 3904 \times 2.16 \times 1.54/5.85 + 6518 \times 1.54/5.85 + 7673 \times 1.54/5.85 = 5959 \text{ KN-m}$$

$$S.F = 3904 \times 2.16/5.85 + 6518/5.85 + 7673 \times 4.31/5.85 = 8208 \text{ KN M/Width} = 8208/13 =$$

631 KN-m ,

$$M_u = 947 \text{ KN-m/m}$$


$$S.F/Width = 631 \text{ KN} , V_u = 946.5 \text{ KN/m} T_u = 946.5 \times 10^3/1000 \times 950 =$$

$$0.996 \text{ M/mm}^2$$


$$M_u/bd^2 = 947 \times 10^6/1000 \times 950^2 = 1.049 , p_t = 0.2$$

Provide = 16 $\phi$ @ 100 c/c pathway at bottom Provide 12  $\phi$ @100 c/c pathway at top.

### Analysis of Girder with Staad Pro



All units in meter(m)



$$P = 12000 \text{ KN}, e_1 = e_3 = 0, e_2 = 1.2 \text{ m}$$

**P= 12000 kN , e1 =e3 = 0 ,e2 = 1.00 m**

Using Freyssinet system drainage type 27K15 ( 27 stands of 15.0 mm diameter) in 110 mm cable ducts.

Permissible Tensile Capacity of each cable =  $27 \times 0.75 \times 265 = 5366$  kN

The cables are arranged in parabolic profile with end eccentricity zero and central eccentricity is 1000 mm.

Post stressing force required = 12500 kN

Post stressing force at Jack Level =  $12500 \times 1.1 = 13750$  kN

Provide 3 cables

Post stressing force in each cable = 4583 kN < 5366 kN

Safe

### Base Pressure Calculations

Moment at base of well =  $53.74 \times 18 = 3582$  kNm

Total Moment =  $3888 + 3582 = 7470$  kNm

Total vertical Load when half well is empty =  $29826 - 4341 = 25485$  kN


MOI =  $\pi/64 \times 6.5^4 + 6.5 \times 6.5^3/12 = 237.4$  m<sup>4</sup>

Beam pressure with BG =  $25485/75.43 + 7470 \times 3.25 / 237.4 = 440$  kN/m<sup>2</sup> <  $400 \times 1.5$  kN/m<sup>2</sup> Beam pressure

without BG =  $25485/75.43 + 3888 \times 3.25 / 237.4 = 391.1$  kN/m<sup>2</sup> > 400 kN/m<sup>2</sup>

Safe

### Design Cross Beam




Given

Depth of beam	=	1.4	m
Thickness of beam	=	0.4	m
Density of concrete, $\gamma_c$	=	25	kN/m <sup>3</sup>
Thickness of slab	=	0.25	m
Thickness of W.C.	=	0.1	m
Density of W.C.	=	22	kN/m <sup>3</sup>
Length of span, $l_x$	=	20.6	m

Step1:- Dead Load:

Spacing of Main girder / Beam	=	3	m
Weight of rib of x- beam	=	$1.4 \times 0.4 \times 25$	
	=	14	kN/m
Weight of ( Slab + W.C.)	=	$0.25 \times 25 + 0.1 \times 22$	
	=	8.45	kN/m <sup>2</sup>
Total load of deck slab	=	$8.45 \times 2 \times 0.5 \times 3 \times 3/2$	
	=	38.03	kN



This load is assumed length

Load per meter run due to deck slab

$$= 38.025/3$$

$$= 12.68 \text{ kN/m}$$

Total dead load per meter run =  $14+38.025 = 26.7 \text{ kN/m}$

This load is assumed uniformly distributed along

This cross - girder


The reaction on each longitudinal girder

$$= 26.7 \cdot 2 \cdot 3/3$$

$$= 53.4 \text{ kN}$$

Step2:- Live Load:

Class AA (tracked) vehicle produce maximum B.M. and S.F. in x- girder.



This position - girder.

Magnitude of reaction =  $700 \cdot 19.7/20.6$

$$= 670 \text{ kN}$$

No. of long. Beam 3

Because x-girder is rigid, reaction on each longitudinal girder

$$= 700/3 = 233.3 \text{ kN}$$

Maximum bending moment occurs under track load,

$$= 700 \cdot 1.975/3$$

$$= 460.8 \text{ kN-m}$$

Impact factor = 1.1

Including, Impact factor +ve B.M. due to live load

$$= 460.83 \cdot 1.1$$

$$= 507 \text{ kN-m}$$

B.M. due to dead load at a distance of 1.975 from support

$$= 53.4 \cdot 1.975 - (26.675 \cdot (1.975/2)^2)$$

$$= 80 \text{ kN-m}$$

Total Bending Moment =  $507+80$


$$= 587 \text{ kN-m}$$

Step3:- Live Load shear including =  $700 \cdot 1.1/3$

Impact	= 257	kN
Dead Load shear	= 53.35	kN
Total shear for depth	= 53.35+257	
	= 310.4	kN
Clear cover	= 40	mm
Diameter	= 25	mm
Step4:- Effective depth	= 1650-(40+25/2)	
	= 1598	mm
	= 0.16	m
Step5:- Check for shear:		
	b = 400	mm
	$T_v = 310.35 \cdot 1000 / 400 \cdot 1597.5$	
	= 0.486	N/mm <sup>2</sup>
Spacing of 12Φmm , 2 – legged s		
Using 12mm diameter bar	= 12	mm
	$A_{sv} = 2 \cdot 0.785 \cdot 12^2$	
	= 226	mm <sup>2</sup>
	$\sigma_{sv} = 200$	
Spacing of stirrups . Sv	= 200*226*1597.5/310.35*1000	
	232.7	mm <sup>2</sup>
Area of steel required :-		
	$A_{st} = 587 \cdot 10^6 / 0.9 \cdot 1597.5 \cdot 200$	
	= 2041	mm <sup>2</sup>
Minimum shear reinforcement	= 226/400*0.0015	
	= 377	mm <sup>2</sup>
Provide 2L- 12 dia @100mm c/c		
Provide 4-25 dia throughout at top & bottom provide 4-25 dia at mid span at bottom provide 4-25 dia at top on supports		



## Design of Return Wall



Given

$\phi =$	$30^\circ$
$\gamma =$	$19.5 \text{ kN/m}^3$
$h =$	$5 \text{ m}$
$l_t$	$= 2.5 \text{ m}$
$l_h$	$= 0.5 \text{ m}$
$a_1$	$= 0.4 \text{ m}$
$a_2$	$= 0.25 \text{ m}$
$t_s$	$= 0.65 \text{ m}$
$t_b$	$= 0.9 \text{ m}$
$\gamma_c$	$= 25 \text{ kN}$
Live load	$= 75 \text{ kN}$
$f_{ck}$	$= 30$
$f_y$	$= 415$

Step1:-

$\kappa_a$	$= (1 - \sin\phi) / (1 + \sin\phi)$
$\sin\phi =$	$0.5$
$\kappa_a$	$= 0.33$
$b$	$= 3.65 \text{ m}$

Step2:-

S.No.	Description	Vertical load	Horizontal load	Lever Arm	Clockwise moment	clockwise moment
1	Steam (Rectangular portio	$= a_1 \cdot h \cdot \gamma_c 50$		0.95	47.5	
2	Steam (Triangular portion =	$0.5 \cdot h \cdot 15.625$		0.667	10.422	
3	Base slab	$= b \cdot t_b \cdot \gamma_c 82.125$		1.825	149.878	
4	Earth fill	$= h \cdot l_t \cdot \gamma 243.75$		2.4	585	
5	Live load	$= 75 \cdot 75$		2.4	180	
6	Earthfill Horizontal		81.25	1.667		135.44
7	Live load Horizontal		80	2.5		200
	Total	466.5	161.25		972.8	335.44

stem thickness at base (d) required	=	$\frac{1.5 \times 335.42 \times 10^6}{30 \times 1000 \times 0.136}$	
	=	351.2 mm	
provided (d)	=	590 mm	safe
b	=	1000 mm	
stem thickness at base(d)	=	590 mm	
R	=	1.445	
	=	$\frac{fck}{2 \times fy} \times \left[ 1 - \frac{\sqrt{1 - 4.6 \times R}}{fck} \right]$	
% of steel	=	0.004255	%
Ast required	=	2510.45	mm <sup>2</sup>
Check	=	For shear at base of stem	
Zv	=	$1.5 \times V / b \times d$	
	=	0.41	
Z v < Zc		Safe .	

### Design of Parapet:-

Horizontal load = 150 kg/m<sup>2</sup>


Width of wall considered = 1 m

B.M. = 0.5\*150\*1

6

1.5\*0. x10

= 75 kg-m

  
=30x1000.75x0KN.136-m

M.O.R. = 0.136\*f<sub>ck</sub>\*b\*stem thickness at base(d)<sup>2</sup>

d required = 16.6 mm

Provide nominal 100mm thick parapet with 10dia @ 150 c/c vertically on each face and 8 dia @ 150 c/c horizontally on each face.